



Eigenschaften

Baureihe	050 Signal- und Beleuchtungstechnik für Schaltkästen
Komponent	Zusammenstellbare Meldeleuchtensäulen
Typ	Lineare Led-Deckenleuchte, 110÷240V AC, 50/60HZ, 1300 lux
Artikel-Nr.	050PEL3C
Beschreibung	Lineare Led-Deckenleuchte, 110-240V AC, 50/60HZ, 1300 lux, L 368 mm, mit Verbinder
Farbe	Grau RAL7035
Gewicht - gr	349,000
Zolltarifnummer	85122000
GTIN	8052878049256

Technische Angaben

Approvals	CE
Compliance with standards	IEC-EN60598-1, IEC-EN60598-2-1, IEC-EN61347-1
Compliance with standards	IEC-EN61347-2-13, IEC-EN62471, IEC-EN55015,
Compliance to EMC standards	IEC-EN61547, IEC-EN61000-3-2, IEC-EN61000-3-3
Compliance to directives	2014/35/UE, 2006/42/EC, 2014/30/UE, RoHS 2002/95
Operating temperatures	-40° ÷ +70°C
Environmental operating values	"all climates" +40°C and 92% RH
Protection degree	IP30 (IEC-EN60529)
Protection against impact	IK06 (IEC-EN62262)
Housing material	PC Polycarbonate
Overvoltage category	Class II (IEC-EN61140)
LED brightness - Power consumption	Lux 1300 - 6W
Operating voltage tolerance	+10% / -20%
LED electrical life	50.000 hours
LED colour temperature	6000K
Rated insulation voltage	Ui 300V - Uimp 2.5kV
On-Off switch	Built-in
Light distribution	Rotation of 180° - adjustable
Power supply connector	050C7V2 included, suitable for single lamp wiring
Power supply connector	or sequential wiring of max n°5 lamps
Light up possibility	Through door limit switch - 050F02S

050PEL3C

Lineare Led-Deckenleuchte, 110-240V AC, 50/60HZ,
1300 lux, L 368 mm, mit Verbinder

Accessory	050KFM Magnetic mounting kit
Warranty period	18 months

Technische Zeichnungen

