



Main

Range	Acti 9
Product name	Acti 9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	3P + N

Complementary

[In] rated current	2 A 4 A 6 A 10 A 16 A 20 A 25 A
Fuse curve	AM GG
Fuse size	10.3 x 38 mm
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	75 mm
Colour	White
Connections - terminals	Screw clamp terminals1 cable(s) 0.75...10 mm ² rigid Screw clamp terminals1 cable(s) 0.5...6 mm ² flexible Screw clamp terminals2 cable(s) 0.75...4 mm ² rigid Screw clamp terminals2 cable(s) 0.5...6 mm ² flexible

Wire stripping length	12 mm
Tightening torque	2 N.m

Environment

Standards	IEC 60269-1/2 IEC EN 60947-3
IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins