



Main

Range	Acti 9
Product name	Acti 9 SBI
Product or component type	Fuse-disconnector
Device short name	SBI
Poles description	3P

Complementary

[In] rated current	10 A 16 A 20 A 25 A 32 A 12 A 40 A 50 A
Fuse curve	GG AM
Fuse size	14 x 51 mm
[Ue] rated operational voltage	690 V AC
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	9
Connections - terminals	Screw clamp terminals1 cable(s) 2.5...25 mm ² rigid Screw clamp terminals1 cable(s) 2.5...25 mm ² flexible
Tightening torque	3.5 N.m

Environment

Standards	IEC EN 60947-3
Pollution degree	3
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	360 g
Package 1 Height	7.7 cm
Package 1 width	8 cm
Package 1 Length	11.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Weight	780 g
Package 2 Height	8 cm
Package 2 width	12 cm
Package 2 Length	17 cm
Unit Type of Package 3	S03
Number of Units in Package 3	24
Package 3 Weight	9.847 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------