

module PE/N (32146)



Description

Article

Part No.: 32146

module PE/N

attachable to busbar adapter on both sides

18 x 242

for busbars 12, 15, 20, 25, 30 x 5, 10 and section busbars

System

60Classic

Product group 05

Subgroup 43

pack size 4

EAN 4021267321468

catalog page 2019 : 3.12

eCl@ss 6.1 27370304

eCl@ss 7.1 27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Approvals

Standards

IEC 61439-1:2011

GB/T 7251.1

Approvals

UL



type number: 680.1

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>

Product data

Details IEC

Standards

IEC 61439-1:2011

GB/T 7251.1

Electrical data IEC

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 690 V

power dissipation of the article:

The power dissipation at a typical load of 80% of the rated current results to 0.9 W.

(The power dissipation for operation with rated current would be 1.4 W.)

Connecting terminals 16 mm² top and bottom

Details UL

Standards

UL 508

Mechanical data

W x H x D: 18 x 242 x 50

weight: 14.1 kg/100

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars

Torque for busbar contacting 12Nm

Torque for pipe connection 40Nm

Reference

For feeding and tapping the PE/N busbar

version is without connection leads

assembly on the 60mm-System only possible in conjunction with an adapter or device carrier

both sides can be plugged onto all adapters, device carriers and side-mounted modules.