

## busbar 20 x 10 (01624)



### Description

#### Article

Part No.: 01624  
busbar 20 x 10  
length 2.40 m, tinned

#### System

60Classic

**Product group** 06

**Subgroup** 83

**pack size** 1

**EAN** 4021267016241

## Advantages of the product

Tin-plated Cu busbars considerably reduce the effort of preparing the contact points.  
The Cu busbars are effectively protected against aggressive media.

catalog page 2019 : 3.3

eCl@ss 6.1 27370303

eCl@ss 7.1 27370303

ETIM 4.0 EC001522

ETIM 5.0 EC001522

## Approvals

### Standards

IEC 61439-1:2011

GB/T 7251.1

### Approvals

CSA , UL , DNV GL



for UL feeder circuits >250V

type number: 20x10-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

CCC approval: no certification required

## Product data

### Details IEC

#### Standards

IEC 61439-1:2011

GB/T 7251.1

### Electrical data

Please respect the insulation characteristics of the busbar support for your application.

short-circuit withstandability: see product description of the used busbar support

current at 30 K 520 A

:

## Details UL

### Standards

UL 508

for UL feeder circuits >250V

considering the permitted temperature rise at the concrete installation conditions the following capacity could be accepted by UL (file E197039

max. load acc. to UL 508: 564 A

Notice the rated voltage of the used busbar support in the application.

## Mechanical data

L x W x D: 2400 x 20 x 10

weight: 428.6 kg/100

cross-section: 200 mm<sup>2</sup>


Edge radius 0.5

## Material properties

Main body: Cu-ETP R300 (EN 13601), tinned

corrosion-resistant, also in aggressive environments

## Accessories



### **01245**

busbar cover  
for 12 - 30 x 10 busbar, 1 m long  
touch protection cover



### **37212**

current transformer 200 A / 5 A  
2.5 VA / class 1

when used on busbars or in adapters 630 A additional 37900 required.



### **NEW**

### **37213**

current transformer 250 A / 5 A  
2.5 VA / class 1

when used on busbars or in adapters 630 A additional 37900 required.



### **NEW**

### **37214**

current transformer 400 A / 5 A  
2.5 VA / class 1

when used on busbars or in adapters 630 A additional 37900 required.



### **NEW**

### **37215**

current transformer 500 A / 5 A  
2.5 VA / class 1

when used on busbars or in adapters 630 A additional 37900 required.

### **NEW**

**37216**

current transformer 600 A / 5 A

2.5 VA / class 1

when used on busbars or in adapters 630 A additional 37900 required.

**NEW**